

LED PANEL LIGHT

↑ Indoor

AURIO LED Panel light solutions are specifically designed to easily replace current conventional products and provide Commercial-Grade significant advantages. They are available in Residential and options.

- 90% uniformity across the emitting surface.
- High quality LED chips with 9000hrs LM-80 certification.
- High efficacy up to 103lm/W.
- High quality Aluminum PCB for thermal dissipation.
- 1-10V dimming standard.



Model #	Input Voltage	Wattage	Lumen	Lumen Efficacy	CCT	CRI	PF	Cert.	Rated life
SYH-22-36WD-100-40-2835	AC100-277V	36W	3708Lm	103Lm/W	4000/5000K	>80	>0.9	DLC4.0	50,000hrs.
SYH-22-40WD-100-40-2835	AC100-277V	40W	4120Lm	103Lm/W	4000/5000K	>80	>0.9	DLC4.0	50,000hrs.
SYH-22-46WD-100-40-2835	AC100-277V	46W	4738Lm	103Lm/W	4000/5000K	>80	>0.9	DLC4.0	50,000hrs.
SYH-24-52WD-100-40-2835	AC100-277V	52W	5356Lm	103Lm/W	4000/5000K	>80	>0.9	DLC4.0	50,000hrs.
SYH-24-60WD-100-40-2835	AC100-277V	60W	6180Lm	103Lm/W	4000/5000K	>80	>0.9	DLC4.0	50,000hrs.

Dimensions and Weight

Model #	Length	Width	Height 1	Height 2	Net Weight(lbs)
SYH-22-36WD-100-40-2835	23.77	23.77	0.39	1.97	7.32
SYH-22-40WD-100-40-2835	23.77	23.77	0.39	1.97	7.32
SYH-22-46WD-100-40-2835	23.77	23.77	0.39	1.97	7.32
SYH-24-52WD-100-40-2835	47.79	23.77	0.39	1.97	14.55
SYH-24-60WD-100-40-2835	47.79	23.77	0.39	1.97	14.55

